

For demonstration and consultation:
Impianti Sdn Bhd

Contact: +603 5124 6200
info@impianti.com.my
www impianti.com.my



G-Force™ II Pressure Washers

Graco's Complete Line of Professional Pressure Washers



PROVEN QUALITY. LEADING TECHNOLOGY.



Graco has the **RIGHT SOLUTIONS** for all your pressure washing applications.

Graco understands how you work and what you demand to get the job done. Whether you need a pressure washer for the occasional cleaning job, one designed with high flow and pressure for weekly use, or one that's designed for tough, day-long cleaning and surface preparation jobs, Graco has a pressure washer that's ideally suited for you. Use this chart below to help you determine the size and capability that best meets your needs.



PRESSURE WASHING SOLUTIONS GUIDE

CLASSIFICATION:	LIGHT DUTY	CONTRACTOR DUTY	HEAVY-DUTY
WEEKLY USAGE (HRS)	2 – 10	10 – 20	20 – 30
PRESSURE PSI (BAR)	2,500 – 3,000 (172 - 207)	3,000 – 4,000 (207 - 276)	4,000 (276)
FLOW (GPM)	2.5 – 3 (9.5 - 11.4)	3 – 4 (11.4 - 15.1)	4 (15.1)
DRIVE TYPE	Direct	Direct	Belt
PUMP TYPE	Axial Piston or Forged Brass Triplex	Forged Brass Triplex	Forged Brass Triplex
UNLOADER	Integrated, Variable Pressure	External, Variable Pressure	External, Variable Pressure
FEATURES:	LIGHT DUTY	CONTRACTOR DUTY	HEAVY-DUTY
NON-MARKING HOSE	25 or 50 ft Non-Marking (7.5 or 15 m)	50 ft Non-Marking (15 m)	50 ft Non-Marking (15 m)
HIGH PRESSURE GUN AND WAND	Standard Gun 36 in (92 cm) Wand	Professional Grade Gun 36 in (92 cm) Wand with Quick-Connects	Professional Grade Gun 36 in (92 cm) Wand with Quick-Connects
SPRAY TIPS	4	5	5
CHEMICAL INJECTOR KIT	Yes	Yes	Yes
50-MESH INLET STRAINER	Yes	Yes	Yes
PUMP SAVER THERMAL VALVE	Yes	Yes	Yes
EZ-START PRESSURE RELIEF	No	Yes	Yes
MODELS	G-Force II 2525 DD G-Force II 2532 DD G-Force II 3027 DD	G-Force II 3032 DD G-Force II 4040 DD G-Force II 4040 DDC	G-Force II 4040 BD G-Force II 4040 BDC



Direct Drive • Light Duty

The G-Force II 2525 DD, 2532 DD, and 3027 DD are the best choices for medium duty applications.

They're light, compact, and the perfect choice when you need consistent reliability for the occasional cleaning job.

G-Force II 2525 DD

DESCRIPTION	PART #
G-FORCE II 2525 DD	24U626
SPECIFICATIONS	
OPERATING PSI (BAR):	2500 (172)
HONDA ENGINE (HP):	GC190 (4.6)
FLOW RATE GPM (LPM):	2.5 (9.5)
PUMP TYPE:	AR Radial Axial, Aluminum HD

G-Force II 2532 DD

DESCRIPTION	PART #
G-FORCE II 2532 DD	24U619
SPECIFICATIONS	
OPERATING PSI (BAR):	3200 (221)
HONDA ENGINE (HP):	GX200 (5.5)
FLOW RATE GPM (LPM):	2.5 (9.5)
PUMP TYPE:	AR Radial Axial, Brass HD

G-Force II 3027 DD

DESCRIPTION	PART #
G-FORCE II 3027 DD	24U620
SPECIFICATIONS	
OPERATING PSI (BAR):	2700 (186)
HONDA ENGINE (HP):	GX200 (5.5)
FLOW RATE GPM (LPM):	3.0 (11.4)
PUMP TYPE:	General Triplex

- G-FORCE II 2525 DD, 2532 DD AND 3027 DD INCLUDES
- High-pressure Gun and Wand
 - 25 ft Non-marking Hose (2525 DD)
 - 50 ft Non-marking Hose (2532 DD and 3027 DD)
 - 50 Mesh Inlet Filter
 - Chemical Injector Kit
 - 4 Quick-Connect Spray Tips (0°, 15°, 25°, Chemical)



2525 DD model



2532 DD model

3027 DD model

POWERED by **HONDA**



Features

Heavy-Gauge Aluminum Frame

- ▶ Compact, durable and lightweight for easy loading and maneuverability
- ▶ Resists corrosion from water and chemicals—*will not rust like steel!*
- ▶ Lifetime frame warranty

Honda® Engine

- ▶ Honda GC and GX series engines deliver trouble-free performance
- ▶ Oil Alert automatically shuts down the engine in the event of low oil and prevents engine damage (2532 DD and 3027 DD models only)

Direct Drive Pump

- ▶ Lightweight, compact AR axial piston pump (2525 DD and 2532 DD models)
- ▶ Higher output general triplex plunger pump with forged brass manifold (3027 DD)
- ▶ Thermal sensor prevents pump from overheating in bypass mode

Integrated Pressure Unloader

- ▶ 3032 DD: adjust pressure to match the application
- ▶ 2525 DD, 2532 DD: presión fijada para lograr un rendimiento uniforme



Direct Drive • Contractor Duty

Built tough to handle weekly use, the G-Force II 3032 DD, 4040 DD and 4040 DDC deliver high flow and pressure in a compact, durable package.

G-Force II 3032 DD

DESCRIPTION
G-FORCE II 3032 DD

PART #
24U621

SPECIFICATIONS

OPERATING PSI (BAR): 3200 (221)

HONDA ENGINE (HP): GX270 (8.5)

FLOW RATE GPM (LPM): 3.0 (11.4)

PUMP TYPE: General Pump
Triplex

G-Force II 4040 DD

DESCRIPTION
G-FORCE II 4040 DD

PART #
24U622

SPECIFICATIONS

OPERATING PSI (BAR): 4000 (276)

HONDA ENGINE (HP): GX390 (11.7)

FLOW RATE GPM (LPM): 4.0 (15.1)

PUMP TYPE: General Pump
Triplex

G-Force II 4040 DDC

DESCRIPTION
G-FORCE II 4040 DDC

PART #
24U623

SPECIFICATIONS

OPERATING PSI (BAR): 4000 (276)

HONDA ENGINE (HP): GX390 (11.7)

FLOW RATE GPM (LPM): 4.0 (15.1)

PUMP TYPE: Cat Triplex

G-FORCE II 3032 DD, 4040 DD AND
4040 DDC INCLUDES

- High-pressure Gun and Wand with Quick-Connect Fittings
- 50 ft Non-marking Hose
- 50 Mesh Inlet Filter
- Chemical Injector Kit
- 5 Quick-Connect Spray Tips (0°, 15°, 25°, 40°, Chemical)



POWERED by **HONDA**



3032 DD model



4040 DD model



4040 DDC model

Features

Heavy-Gauge Aluminum Frame

- ▶ Compact, durable and lightweight for easy loading and maneuverability
- ▶ Resists corrosion from water and chemicals
- ▶ Lifetime frame warranty—*will not rust like steel!*

Honda Engine

- ▶ GX series industrial-grade engine delivers trouble-free performance
- ▶ Oil Alert automatically shuts down the engine in the event of low oil and prevents engine damage

Direct Drive Pump

- ▶ High-performance, compact Triplex Plunger pump mounted directly to the engine
 - DD models: General Triplex Pump
 - 4040 DDC model: Cat Triplex Pump—the most durable, longest-lasting pump in the industry
- ▶ Thermal Relief Valve protects pump from overheating

External Variable Pressure Unloader

- ▶ Adjust pressure to match the application
- ▶ Allows more water into the system to protect against overheating
- ▶ Extremely durable

EZ Start Pressure Relief

- ▶ Eliminates back pressure for easy engine starting





Belt Drive • Heavy-Duty

The G-Force II 4040 BD and 4040 BDC pressure washers are Graco's top-of-the-line units, designed to tackle the toughest cleaning jobs. With the highest performance available for tough, day-long cleaning and surface preparation jobs, these models can easily handle even the most demanding jobs.

G-Force II 4040 BD

DESCRIPTION **PART #**
 G-FORCE II 4040 BD 24UG24

SPECIFICATIONS
OPERATING PSI (BAR): 4000 (276)
HONDA ENGINE (HP): GX390 (11.7)
FLOW RATE GPM (LPM): 4.0 (15.1)
PUMP TYPE: General Pump
 Triplex

G-Force II 4040 BDC

DESCRIPTION **PART #**
 G-FORCE II 4040 BDC 24UG25

SPECIFICATIONS
OPERATING PSI (BAR): 4000 (276)
HONDA ENGINE (HP): GX390 (11.7)
FLOW RATE GPM (LPM): 4.0 (15.1)
PUMP TYPE: Cat Triplex

G-FORCE II 4040 BD AND 4040 BDC INCLUDES

- High-pressure Gun and Wand with Quick-Connect Fittings
- 50 ft Non-marking Hose
- 50 Mesh Inlet Filter
- Chemical Injector Kit
- 5 Quick-Connect Spray Tips (0°, 15°, 25°, 40°, Chemical)



4040 BD model



4040 BDC model

POWERED by **HONDA**



Features

Heavy-Gauge Aluminum Frame

- ▶ Compact, durable and lightweight for easy loading and maneuverability
- ▶ Resists corrosion from water and chemicals—*will not rust like steel!*
- ▶ Lifetime frame warranty

Honda Engine

- ▶ GX series industrial-grade engines deliver trouble-free performance
- ▶ Oil Alert automatically shuts down the engine in the event of low oil and prevents engine damage



Belt-Driven Pump

- ▶ Tri-belt design for improved durability
- ▶ Triplex Plunger Pump runs slower and cooler for increased durability
 - 4040 BD model: General Triplex Plunger Pump
 - 4040 BDC model: Cat Triplex Plunger Pump—the most durable, longest-lasting pump in the industry
- ▶ Thermal Relief Valve protects pump from overheating

External Variable Pressure Unloader

- ▶ Adjust pressure to match the application
- ▶ Allows more water into the system to protect against overheating
- ▶ Extremely durable

EZ Start Pressure Relief

- ▶ Eliminates back pressure for easy engine starting